



CINEMILLS.COM

SHOWROOM & MAIN OFFICE
2021 N. LINCOLN ST.
BURBANK, CA 91504

OFFICE: 818.843.4560
SALES@CINEMILLS.COM



CINESOFT 1x1 (CSOFT400)



SPECIFICATIONS	
Color temperature	3200K~5600K
Brightness 3200K	1050Lux at 1M
Brightness 5600K	1280Lux at 1M
Beam angle	120°
Power consumption	70Watt
Input power	100V~240V AC/DC Adaptor or DC12V~24V
Dimming	0%~100%
Dimension	16x12.5x4 Inches (415x315x98mm)
Weight	6lbs (2.9Kg)
Controls	
Display	4Digit 7 Segment
Indicator	Manual, DMX, Address
Tact Switch	Mode, UP, Down
Round V.R	Color Temp., Dim.
Lock Switch	Power
Slide Switch	Terminate of DMX
Connection	
DMX IN	XLR 5P Male
DMX OUT	XLR 5P Female
DC INPUT(12V~24V)	XLR 4P Male
Accessories	
RB400R-CS	Removable Barndoor Set
HC400R-CS	Honeycomb Grid (60%)
VM400R-CS	V-Mount Battery Adapter Plate
SC600R-CS	Soft Case – Carry On

ACCESSORIES

